

PROCEDURE OF LAPPING GLOVE VALVES

Ebook

Procedure of Lapping Glove Valves

Lapping glove valves is a critical process in ensuring tight seals and optimal performance of valves used in various industrial applications. Proper lapping not only enhances the sealing surface but also extends the lifespan of the valve by preventing leaks and ensuring smooth operation. This article provides a comprehensive guide on the procedure of lapping glove valves, covering the necessary tools, safety precautions, step-by-step instructions, and best practices to achieve the best results.

Understanding the Lapping Process for Glove Valves

Lapping is a precision machining process that involves rubbing two surfaces together with an abrasive material to achieve a smooth, flat, and perfectly fitting contact surface. When it comes to glove valves, the process focuses on the sealing surfaces, such as the valve seat and the valve face, to eliminate imperfections and ensure a tight seal.

Tools and Materials Required

Before starting the lapping procedure, gather the following tools and materials:

- Valve and valve seat (the component to be lapped)
- Valve lapping compound (abrasive paste)
- Rubber or glove lap (lapping tool)
- Cleaning brushes and rags
- Lubricant or water (for cooling and lubrication)
- Protective gloves and safety goggles
- Measuring tools (feeler gauges, magnifying glass)
- Workbench or stable work surface

Preparation Steps

1. Safety Precautions

Prior to beginning, always prioritize safety:

- Wear protective gloves to avoid contact with abrasive compounds.
- Use safety goggles to shield eyes from debris.
- Work in a well-ventilated area to avoid inhaling dust or fumes.
- Ensure the work area is clean and free of clutter.

2. Disassembly of the Valve

Carefully remove the glove valve from its assembly:

- Loosen and remove bolts or screws holding the valve in place.
- Separate the valve from the pipeline or housing, taking care not to damage the sealing surfaces.
- Inspect the valve for any damages or corrosion that may need attention before lapping.

3. Cleaning the Valve Components

Thorough cleaning ensures no debris or old lapping compound remains:

- Use brushes and cleaning solvents to remove grease, dirt, or residues.
- Dry all parts completely before proceeding.

Step-by-Step Procedure of Lapping Glove Valves

1. Applying the Lapping Compound

The lapping compound is the abrasive agent that facilitates surface smoothing:

- Choose an appropriate abrasive grade based on the condition of the sealing surfaces. Coarser grits are used for initial lapping, finer grits for finishing.
- Apply a small amount of lapping compound evenly on the valve seat or face.
- Ensure coverage over the entire sealing surface for uniform results.

2. Mounting the Valve in the Lapping Tool

Secure the component for effective lapping:

- Place the valve face or seat against the rubber or glove lap, which acts as a soft, conforming abrasive surface.

- Be gentle but firm to avoid damaging the component.
- Ensure the valve is aligned properly to prevent uneven lapping.

3. Lapping Movement and Technique

Perform consistent and controlled movements:

- Gently rotate or move the valve back and forth over the lap surface, maintaining a steady pressure.
- Use uniform circular or figure-eight motions to promote even material removal.
- Maintain consistent pressure throughout the process; avoid applying excessive force which may damage the component.
- Periodically check the progress by inspecting the surface for smoothness and uniformity.

4. Cooling and Lubrication During Lapping

To prevent overheating and ensure smooth operation:

- Use water or a suitable lubricant during lapping to reduce friction and carry away debris.
- Keep the surfaces moist to facilitate finer finishing and prevent scratches.
- Reapply the lapping compound as needed to maintain abrasive action.

5. Inspecting Progress and Surface Quality

Regular inspection is vital:

- Use a magnifying glass or visual inspection to check for scratches, pits, or uneven areas.
- Use feeler gauges or a straightedge to verify flatness and contact surface quality.
- Ensure the sealing surface appears uniform and free of irregularities.

6. Final Finishing and Cleaning

Once the desired surface finish is achieved:

- Remove the valve from the lap surface carefully.
- Clean all residual abrasive compounds thoroughly with clean water and brushes.
- Dry the component completely to prevent corrosion.

Reassembly and Testing

After lapping, reassemble the glove valve:

- Carefully reinstall the valve into its housing, ensuring proper alignment.
- Torque bolts or screws to manufacturer specifications.
- Conduct pressure tests or leak tests to verify the integrity of the seal.

Best Practices for Effective Lapping of Glove Valves

To ensure optimal results, consider these best practices:

- Use appropriate abrasive grades: start with coarse grit for removing imperfections, then progress to finer grits for finishing.
- Maintain consistent pressure and motion during lapping to promote uniform surface finish.
- Always clean components thoroughly after lapping to remove abrasive residues.
- Inspect regularly to prevent over-lapping, which can remove too much material.
- Document the process and findings for quality control and future reference.

Conclusion

The procedure of lapping glove valves is a meticulous process that requires patience, precision, and adherence to safety standards. Properly executed lapping enhances the sealing surfaces, ensuring leak-proof operation and extending the lifespan of the valve. By following the detailed steps outlined? from preparation and disassembly to the actual lapping and final inspection? technicians can achieve superior results and maintain high-quality standards in valve maintenance and repair. Remember, the key to successful lapping lies in careful surface preparation, appropriate abrasive selection, consistent technique, and thorough cleaning, all contributing to a reliable and efficient valve system.

Procedure of Lapping Glove Valves: A Comprehensive Guide

In the realm of industrial maintenance and mechanical engineering, the procedure of lapping glove valves plays a crucial role in ensuring optimal sealing performance and extending the lifespan of valve components. Glove valves, often used in chemical processing, pharmaceutical manufacturing, and other critical systems, require precise sealing surfaces to prevent leaks, contamination, or pressure loss. Lapping, a meticulous process of fine machining and polishing, is employed to achieve a smooth, flat, and leak-proof contact surface between the valve disc and seat. This guide aims to provide a detailed, step-by-step overview of the lapping procedure for glove valves,

highlighting best practices, tools, safety considerations, and troubleshooting tips.

Understanding Glove Valves and the Need for Lapping

What are Glove Valves?

Glove valves are specialized shut-off valves equipped with a flexible, glove-like sealing mechanism, often used to handle hazardous or sterile materials. They feature a body with ports, a sealing mechanism (disc or plug), and a glove-like seal that allows for controlled access to the process line.

Why Lapping is Essential for Glove Valves

Over time and through operation cycles, the sealing surfaces of glove valves can develop imperfections, scratches, or uneven contact points. These irregularities compromise the seal, leading to leaks or contamination risks. Lapping restores the mating surface's flatness and smoothness, ensuring a tight, leak-proof seal.

Preparatory Steps Before Lapping

- Inspection and Assessment
 - Visual Inspection: Examine the valve for signs of damage, corrosion, or pitting on the sealing surfaces.
 - Leak Testing: Conduct a preliminary leak test to identify the severity of surface imperfections.
 - Measurement: Use a surface plate or a dial indicator to check for deviations or unevenness on the sealing surface.
- Disassembly of the Valve
 - Isolate the Valve: Shut off the process line and drain the valve completely.
 - Remove the Valve Body: Carefully disassemble the glove valve, noting the position of all components.
 - Extract the Seat and Disc: Separate the sealing elements for dedicated lapping procedures.
- Cleaning

- Use appropriate solvents or cleaning agents to remove grease, dirt, or residues from the sealing surfaces.
- Dry all parts thoroughly to prevent contamination during lapping.

Tools and Materials Required

- Lapping Compound: A fine abrasive paste, typically silicon carbide or aluminum oxide, suitable for valve sealing surfaces.
- Lapping Plate or Flat Surface: A lapping stone, glass plate, or a dedicated lapping machine with a flat, smooth surface.
- Lapping Stick or Applicator: For applying the lapping compound evenly.
- Clamps or Fixtures: To hold the valve seat or disc securely during lapping.
- Measuring Instruments: Feeler gauges, surface roughness testers, or optical comparators for quality checks.
- Personal Protective Equipment (PPE): Gloves, goggles, and masks to protect against abrasive particles.

Step-by-Step Procedure of Lapping Glove Valves

Step 1: Preparing the Lapping Surface

- Ensure that the lapping plate or surface is clean, flat, and free from debris.
- If using a lapping machine, calibrate it to maintain uniform pressure and rotation.

Step 2: Applying the Lapping Compound

- Place a small amount of fine abrasive paste onto the lapping surface.
- Spread the compound evenly to create a thin, consistent layer.

Step 3: Positioning the Valve Components

- Securely fix the valve seat or disc onto the lapping fixture or directly onto the lapping plate.
- The component should be held firmly to prevent movement during the process.

Step 4: Lapping the Surface

- Gently move the component in a circular or figure-eight pattern over the lapping surface.
- Maintain uniform pressure throughout; avoid excessive force which can cause uneven wear.
- Continue lapping for a period ranging from several minutes to hours, depending on the surface condition.
- Periodically stop to inspect the surface and ensure even removal of material.

Step 5: Checking Progress

- Use feeler gauges or surface inspection tools to assess the flatness and smoothness.
- Look for a consistent, mirror-like finish with no visible scratches or pits.
- Conduct a leak test if possible, to evaluate sealing performance.

Step 6: Cleaning and Final Inspection

- Carefully remove the lapping compound residue from the part using solvents or deionized water.
- Dry thoroughly to prevent corrosion.
- Conduct a final inspection with measuring instruments to confirm surface quality.

Reassembling the Glove Valve

- Once the lapping process is complete and the surfaces are verified to be smooth and flat, reassemble the valve carefully.
- Ensure all components are correctly aligned and seated.
- Use appropriate torque specifications for bolts and fittings.

Testing the Lapped Valve

- Conduct pressure tests to verify leak-tightness.
- Observe for any signs of leakage or malfunction.
- If leaks persist, repeat the lapping process or identify other underlying issues.

Best Practices and Tips

- Consistent Pressure: Apply uniform pressure during lapping to prevent uneven surfaces.
- Patience: Rushing the process can lead to uneven wear; take your time to achieve the desired finish.

- Use Appropriate Abrasives: Select the correct grit size for the stage of lapping?coarser for rough shaping, finer for finishing.
- Document the Procedure: Keep records of the materials used, duration, and inspection results for future reference.
- Safety First: Always wear PPE when handling abrasive materials and chemicals.

Troubleshooting Common Issues

Issue	Possible Cause	Solution
-----	-----	-----
Surface still rough after lapping	Insufficient lapping time or abrasive too coarse	Extend lapping duration; switch to finer abrasive
Uneven surface or dips	Uneven pressure or movement	Maintain consistent pressure; use a controlled lapping machine
Persistent leaks after reassembly	Surface contamination or improper seating	Clean thoroughly; verify seating and alignment

Conclusion

The procedure of lapping glove valves is a critical maintenance task that ensures reliable sealing, prevents leaks, and prolongs the service life of the valve components. By following a systematic approach?careful inspection, precise application of abrasive compounds, controlled lapping, and thorough testing?technicians can restore the valve's sealing surfaces to their optimal condition. While the process requires patience and attention to detail, the resulting improvements in performance and safety make it a worthwhile investment for any facility handling sensitive or hazardous materials. Remember to adhere to safety protocols and manufacturer guidelines throughout the process to achieve the best results.

QuestionAnswer What is the first step in the procedure of lapping glove valves? The first step is to disassemble the valve and clean all components thoroughly to remove any debris or corrosion before starting the lapping process. Which materials are typically used for lapping gloves in valve maintenance? Lapping gloves are usually made from soft, abrasive materials like fine rubber or leather with abrasive compounds to ensure a smooth and uniform finish on valve surfaces. How do you apply the lapping compound during the glove valve lapping process? A small amount of appropriate lapping compound is applied evenly to the valve seat and the sealing surface, ensuring proper coverage for effective lapping without excess. What is the correct technique for lapping glove valves? The correct technique involves rotating and pressing the valve against the seat with

consistent pressure in a circular or elliptical motion to achieve an even, smooth surface finish. How do you determine when the lapping process is complete? Lapping is complete when a uniform, smooth contact surface is achieved, typically confirmed by a consistent leak-tight seal during testing and visual inspection for surface finish. What safety precautions should be taken during the lapping glove valve procedure? Wear appropriate personal protective equipment such as gloves and eye protection, work in a well-ventilated area, and handle abrasive compounds carefully to prevent injury or inhalation of particles. How do you clean the valve components after lapping? After lapping, thoroughly clean all components with solvent or water to remove any residual abrasive material, and dry them properly before reassembly. Why is lapping glove valves important in valve maintenance? Lapping ensures a proper seal and smooth surface contact between the valve and its seat, which improves sealing performance, reduces leakage, and extends the valve's service life.

Related keywords: valve lapping, glove valve repair, valve seat grinding, valve refurbishment, valve sealing, lapping process, valve surface finishing, hand lapping, valve maintenance, sealing surface preparation

removing kia sorento glove box

Removing Kia Sorento Glove Box

Removing the glove box from your Kia Sorento can be a straightforward process if you understand the steps involved and have the right tools at hand. Whether you're replacing the glove box, repairing a latch, fixing electrical components behind it, or performing a general interior maintenance task, knowing how to safely and correctly remove the glove box is essential. This guide provides a comprehensive, step-by-step approach to removing the Kia Sorento glove box, covering different model years and variations to ensure you are well-equipped for the task.

Understanding the Kia Sorento Glove Box Assembly

Before diving into removal procedures, it's important to understand the structure and components of the glove box assembly in a Kia Sorento.

Components of the Glove Box

- Glove Box Door: The front panel that opens and closes.
- Hinges: Attach the door to the dashboard.
- Latch Mechanism: Secures the glove box when closed.

- Mounting Frame: The internal structure holding the glove box in place.
- Electrical Components (if equipped): Such as lighting or sensors behind the glove box.
- Screws and Clips: Fasteners securing the glove box to the dashboard.

Common Variations Across Model Years

- Some Kia Sorento models have a soft-close or soft-close latch.
- Presence of electrical connectors for glove box lighting.
- Differences in latch mechanisms or hinge designs depending on trim and year.

Tools Needed for Glove Box Removal

Having the right tools makes the removal process easier and prevents damage:

- Flat-head screwdriver or plastic trim removal tools
- Phillips-head screwdriver
- Torx screwdriver (if applicable, depending on model)
- Trim removal panel tools (optional but recommended)
- Work gloves (optional for protection)

Preparatory Steps Before Removing the Glove Box

Proper preparation ensures safety and makes the removal process smoother.

1. Park the Vehicle and Turn Off the Ignition

- Ensure the vehicle is parked on a level surface.
- Turn off the engine and remove the key.
- Remove any valuables from the glove box to prevent damage or loss.

2. Disconnect the Battery (Optional but Recommended)

- If your glove box has electrical components (like lighting or sensors), disconnecting the battery reduces the risk of electrical shorts or shocks.
- To do this, disconnect the negative terminal from the battery.

3. Clear the Workspace

- Remove any objects that might obstruct access.
- Use a clean, well-lit area for easy handling of parts.

Step-by-Step Guide to Removing the Kia Sorento Glove Box

The removal process can be broken down into clear, sequential stages:

1. Open the Glove Box

- Fully open the glove box door to access the hinges and interior screws.

2. Remove the Glove Box Door (if necessary)

- Some models require removing the door first to access the mounting screws.
- Locate the hinge pins or screws securing the door.
- Use a flat-head screwdriver or trim removal tool to gently pry off the door, or unscrew hinges if screws are accessible.
- Be cautious to avoid cracking the door or damaging hinges.

3. Remove the Glove Box Liner or Inner Panel

- Inside the glove box, locate screws or clips holding the inner liner in place.
- Use a Phillips-head screwdriver or trim removal tool to carefully detach the liner.
- Disconnect any electrical connectors (lighting, sensors) attached to the glove box liner.
- Set aside the liner and any removed screws.

4. Detach the Mounting Screws/Clips

- Identify the screws or clips securing the glove box assembly to the dashboard.
- These are typically located along the top, sides, or bottom edges of the glove box frame.
- Use appropriate screwdrivers to remove these fasteners.
- Keep screws in a safe place for reinstallation.

5. Detach the Glove Box Assembly

- Gently pull the glove box assembly away from the dashboard.

- Be mindful of any remaining clips or connectors.
- If the glove box is stuck, carefully use a trim removal tool to release clips without damaging surrounding panels.

6. Disconnect Electrical Connections (if present)

- If your glove box has lighting or sensors, disconnect electrical connectors carefully.
- Press the release tabs and gently pull connectors apart.

7. Remove the Entire Glove Box Assembly

- Once all fasteners and connectors are removed, the glove box should come free.
- Carefully extract it from the dashboard, avoiding damage to surrounding panels.

Special Considerations and Tips

Handling Clips and Fasteners

- Many clips are made of plastic and can break if handled roughly.
- Use plastic trim removal tools rather than metal screwdrivers to prevent scratches or cracks.

Electrical Components

- Always disconnect the battery before handling electrical connectors.
- Note the position of connectors for easier reinstallation.

Reinstallation Tips

- Follow removal steps in reverse order.
- Ensure all clips and screws are securely fastened.
- Test electrical components before reassembling the glove box fully.

Common Problems During Removal and How to Address Them

Stuck or Hard-to-Remove Glove Box

- Some glove boxes may be tightly fitted or have stubborn clips.
- Use gentle force and appropriate tools.
- Check for hidden screws or clips you might have missed.

Broken Clips or Fasteners

- Keep spare clips on hand in case replacements are needed.
- Use adhesive or repair kits for minor damages if necessary.

Electrical Connector Difficulties

- Be patient when disconnecting electrical connectors.
- Do not force connectors, as they can be damaged.

Summary

Removing the glove box from your Kia Sorento is a manageable task with proper preparation and care. By understanding the structure of the glove box, gathering the right tools, and following sequential steps, you can safely remove and reinstall the glove box for any repairs or modifications. Always remember to disconnect the battery if electrical components are involved, and handle plastic clips and connectors delicately to prevent damage.

Final Recommendations

- Consult your specific Kia Sorento model's service manual for detailed diagrams and specifications.
- Take your time during removal and reinstallation to ensure all parts are properly secured.
- If unsure or uncomfortable with the process, seek professional assistance to avoid damaging interior panels or electrical components.

By following this comprehensive guide, you should be well-equipped to remove your Kia Sorento's glove box efficiently and safely, paving the way for successful repairs or upgrades.

Removing Kia Sorento glove box is a task that many vehicle owners may find necessary for various reasons—be it to replace a damaged component, access hidden parts, or perform maintenance. Whether you're a seasoned DIY enthusiast or a beginner looking to undertake this project, understanding the proper steps and precautions can make the process smoother and prevent unnecessary damage. In this comprehensive guide, we will explore the entire process of removing

the Kia Sorento glove box, discuss tools required, potential challenges, and tips to ensure a successful removal.

Understanding the Kia Sorento Glove Box

Before diving into removal procedures, it's essential to understand what the glove box assembly consists of in the Kia Sorento. Generally, the glove box is a plastic or metal compartment integrated into the dashboard, providing storage space for documents, manuals, and small items. The assembly includes the glove box door, hinges, latch mechanism, and mounting brackets.

Features of Kia Sorento glove box:

- Usually secured with screws and clips
- Some models have a soft-close or lockable glove box
- Integrated with dashboard trim pieces

Pros of the Kia Sorento glove box:

- Provides convenient storage
- Designed for easy access
- Often includes features like illumination or lock

Cons or challenges:

- Can be fragile if mishandled
- Removal may require dealing with clips and screws that can break
- Some models have complex locking mechanisms

Tools and Materials Needed

Proper preparation is key to a successful glove box removal. Here's a list of common tools and materials you might need:

- Phillips head screwdriver
- Flathead screwdriver or panel removal tool
- Torx screwdriver set (if applicable)
- Trim removal tools

- Needle-nose pliers
- Flashlight (for better visibility)
- Replacement clips or screws (optional, in case of breakage)
- Safety gloves and eye protection

Note: Always ensure you have the correct tools to avoid damaging clips or panels.

Step-by-Step Guide to Remove the Kia Sorento Glove Box

1. Prepare the Vehicle

- Park the vehicle on a flat surface
- Turn off the ignition and remove the key
- Engage the parking brake
- Clear out the glove box to prevent items from falling during removal

2. Access the Glove Box Interior

- Open the glove box door fully
- Examine inside for any screws or clips securing the glove box to the dashboard
- Remove any contents to prevent obstruction

3. Detach the Glove Box Door

- Locate the screws or clips holding the glove box door to its hinges
- Use the appropriate screwdriver to unscrew these fasteners
- Carefully detach the door, supporting it to prevent drops or damage

4. Remove the Glove Box Panel

- Identify the screws securing the glove box assembly to the dashboard frame
- These are usually located along the top and sides of the glove box opening
- Use a Phillips screwdriver or trim removal tool to gently pry away panels if necessary
- Carefully disconnect any electrical connectors (such as glove box light wiring) before fully removing the assembly

5. Detach Mounting Clips and Fasteners

- Locate mounting clips or brackets holding the glove box in place
- Use trim removal tools or flathead screwdrivers to release clips
- Be cautious, as clips can be brittle and may break if too much force is applied

6. Remove the Entire Glove Box Assembly

- Once all fasteners and clips are detached, gently pull the glove box out
- Support the assembly to prevent dropping or damaging surrounding dashboard parts
- Inspect for any remaining connections or screws before completely removing

Tips and Precautions During Removal

- Work Slowly and Carefully: Rushing can cause clips or panels to crack or break.
- Label Fasteners: Keep track of screws and clips, as some may be similar but serve different purposes.
- Use Appropriate Tools: Avoid using excessive force with screwdrivers or prying tools.
- Disconnect Electrical Components Gently: If your glove box has an interior light or lock mechanism connected via wiring, disconnect carefully to prevent damage.
- Protect Surrounding Areas: Use cloth or plastic trim tools to avoid scratching the dashboard.

Common Challenges and How to Overcome Them

Challenge 1: Broken Clips

- Solution: Use replacement clips or retain existing ones carefully. If clips are broken, purchasing replacements from an auto parts store can be a quick fix.

Challenge 2: Hidden Fasteners

- Solution: Consult your vehicle's service manual for specific screw locations. Use a flashlight to improve visibility inside tight spaces.

Challenge 3: Difficult Electrical Connections

- Solution: Disconnect the battery if necessary, especially if dealing with electrical wiring, to prevent shorts or damage.

Challenge 4: Fragile Plastic Components

- Solution: Handle with care, applying gentle pressure. Using trim removal tools minimizes the risk of breaking plastic parts.

Reinstallation and Final Checks

After completing repairs or replacements, reverse the removal process:

- Reconnect any electrical connectors
- Secure the glove box with original screws and clips
- Attach the glove box door and hinges
- Test the operation of the glove box (opening, closing, locking)
- Ensure all panels are flush and secure

Additional Tips for a Smooth Removal Process

- Always consult your vehicle's owner manual or service manual for model-specific instructions.
- Take photos during each step to aid reassembly.
- Work in a clean, organized space to prevent losing small parts.
- If you encounter significant resistance, double-check for hidden fasteners before applying more force.

Conclusion

Removing the Kia Sorento glove box is a manageable task when approached with patience and proper preparation. It involves accessing the interior panels, carefully detaching fasteners, and disconnecting electrical components if present. By following the outlined steps and tips, you can successfully remove the glove box without causing damage, whether for maintenance, repairs, or upgrades. Remember, taking your time and using the right tools will ensure a smooth process and help preserve the integrity of your vehicle's interior components. With this knowledge, you're well-equipped to undertake or assist with glove box removal confidently.

Question How do I remove the glove box from my Kia Sorento? To remove the glove box, first open it fully, then locate and release the retaining clips or screws on the sides or bottom. Carefully pull the glove box out, disconnecting any electrical connections if present. **What tools are needed to remove the Kia Sorento glove box?** Typically, you'll need a Phillips screwdriver or a flat-head screwdriver, and possibly a trim removal tool to safely detach the glove box without

damaging surrounding panels. Are there any safety precautions I should take before removing the glove box? Yes, ensure the vehicle is turned off and the keys are removed. Also, disconnect the negative terminal of the battery if you're disconnecting electrical components to prevent any short circuits. Can I remove the glove box without removing the entire dashboard on my Kia Sorento? Yes, the glove box is designed to be removed independently by releasing its side hinges or screws, without needing to remove the entire dashboard. What are common issues faced when removing the Kia Sorento glove box? Common issues include stuck or broken retaining clips, hidden screws, or electrical connections that require careful handling to avoid damage. How do I access the screws or clips securing the glove box in a Kia Sorento? Open the glove box fully and inspect along the sides and bottom for visible screws or clips. You may need to remove some trim panels to access hidden fasteners. Is there a step-by-step guide available for removing the Kia Sorento glove box? Yes, many online repair guides and videos provide detailed step-by-step instructions specific to your model year. Always refer to the service manual for accurate procedures. Can I reinstall the glove box myself after removal? Absolutely, as long as you keep track of all screws and clips. Follow the reverse procedure of removal, ensuring all connections are secure before closing the glove box.

Related keywords: Kia Sorento glove box removal, Kia Sorento glove box replacement, Kia Sorento glove compartment removal, Kia Sorento glove box repair, Kia Sorento glove box latch, Kia Sorento dashboard removal, Kia Sorento interior repair, Kia Sorento glove box lock fix, Kia Sorento interior parts, Kia Sorento DIY repair

Read the full article online: [Removing kia sorento glove box](#)